

PROJECT \_\_\_\_\_  
 DATE \_\_\_\_\_ JOB# \_\_\_\_\_



PAGE \_\_\_\_\_ OF \_\_\_\_\_  
 REQUESTED BY \_\_\_\_\_

DATE REQUIRED \_\_\_\_\_ CABLE TYPE : MC-AP \_\_\_\_\_ MC \_\_\_\_\_ HCFC \_\_\_\_\_ PHONE # \_\_\_\_\_

TAG #	COMMERCIAL		RESI	IND	HOSP	STD	DECORA		SWITCH VOLTAGE	PLASTER RING 1	AMPERAGE		CABLE LENGTH				NOTES	
	IVORY	GRAY	BRN	BLK	WHT	LT ALMD	15A	20A			MOUNTING 2	SPANNER ADD 3	KICK STAND 4	12/2	12/3	10/2		10/3

1																			
2																			
3																			
4																			
5																			
6																			
7																			
8																			
9																			
10																			
11																			
12																			
13																			
14																			
15																			
16																			
17																			
18																			
19																			
20																			
21																			
22																			
23																			
24																			
25																			
26																			
27																			
28																			
29																			
30																			

**ROUGH-IN READY**  
 11425 CENTURY CIRCLE WEST  
 CINCINNATI, OHIO 45264

800-286-9601 (513) 717-2696 FAX (513) 738-5855  
[www.roughinready.com](http://www.roughinready.com)

- 1 PLASTER RINGS ARE 3/4" UNLESS OTHERWISE NOTED
- 2 ALL ASSEMBLIES WILL INCLUDE A STUD BRACKET UNLESS OTHERWISE NOTED
- 3 SELECT SPANNER BAR LENGTH BY STUD DIMENSION (16" OC OR 24" OC)
- 4 SELECT THE REQUIRED KICKSTAND MOUNTING HEIGHT (MIN. 7" AFF TO MAX 18" AFF)

**QUICK QUOTE \* QUICK SHIP FORM**